

US007352176B1

## (12) United States Patent

#### Roach et al.

# (10) Patent No.: US 7,352,176 B1 (45) Date of Patent: Apr. 1, 2008

### (54) ROTATING CONCAVE EDDY CURRENT PROBE

(75) Inventors: **Dennis P. Roach**, Albuquerque, NM (US); **Phil Walkington**, Albuquerque,

NM (US); Kirk A. Rackow,

Albuquerque, NM (US); Ed Hohman,

Albuquerque, NM (US)

(73) Assignee: Sandia Corporation, Albuquerque, NM

(US)

(\*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

324/228, 234-243

U.S.C. 154(b) by 14 days.

(21) Appl. No.: 11/502,085

(22) Filed: Aug. 10, 2006

(51) **Int. Cl.** 

*G01N 27/82* (2006.01) *G01R 33/12* (2006.01)

See application file for complete search history.

#### (56) References Cited

#### U.S. PATENT DOCUMENTS

5,399,968 A \* 3/1995 Sheppard et al. .......... 324/242

6,014,024 A *	1/2000	Hockey et al 324/240
6,636,037 B1*	10/2003	Ou-Yang 324/240
7 301 335 B2*	11/2007	Sun et al 324/240

#### FOREIGN PATENT DOCUMENTS

GB	2273782	*	6/1994
JP	411148876	*	6/1999
WO	WO 2007/015705	A3	2/2000

\* cited by examiner

Primary Examiner—Reena Aurora
Assistant Examiner—Kenneth J Whittington
(74) Attorney, Agent, or Firm—Robert D. Watson

#### (57) ABSTRACT

A rotating concave eddy current probe for detecting fatigue cracks hidden from view underneath the head of a raised head fastener, such as a buttonhead-type rivet, used to join together structural skins, such as aluminum aircraft skins. The probe has a recessed concave dimple in its bottom surface that closely conforms to the shape of the raised head. The concave dimple holds the probe in good alignment on top of the rivet while the probe is rotated around the rivet's centerline. One or more magnetic coils are rigidly embedded within the probe's cylindrical body, which is made of a non-conducting material. This design overcomes the inspection impediment associated with widely varying conductivity in fastened joints.

#### 20 Claims, 20 Drawing Sheets

